



## SPECIFICATION

Model	JM-450APC	TT-510P	MT-800P
<b>Travel</b>			
X axis mm (inch)	450 (18)	510 (20)	850 (33)
Y axis mm (inch)	350 (14)	400 (16)	500 (20)
Z axis mm (inch)	350 (14)	310 (12)	550 (22)
<b>Spindle</b>			
Main motor (KW)	2.2/3.7 (3.75/5.5)	2.2/3.7 (3.75/5.5)	7.5/11
Max. spindle speed (rpm)	10000 ( 15000/20000)	10000 ( 15000/20000)	10000 (15000)
Spindle taper	BT30	BT30	BT40
<b>Table</b>			
Table dimension mm (inch)	400x300 (16x12 )	600x400 (24x16 )	850x500 (33x20 )
APC change time (sec)	4.5	5	7
Max. table loading kg (lbs)	150 (330)	250 (550)	350 (770)
<b>Feed Rate</b>			
Rapids on X/Y/Z axis mm(inch)/min	32000 (1260)	48000 (1890)	36000 (1417)
Cutting rate mm(inch)/min	15000 (591)	10000 (394)	10000 (394)
<b>Automatic tool changer (Opt.)</b>			
Tool storage capacity (pcs)	10 (20)	14 (20)	24
<b>Machine Size</b>			
Floor space mm (inch)	1420x2275 (56x90)	1600x2800 (63x110)	2,200x3,100 (87x122)
Height mm (inch)	2200 (87)	2425 (95)	2500 (98)
Machine net weight kg (lbs)	2100 (4620)	4000 (8800)	5500 (12100)

( ) optional specification

Specifications are subject to change without notice

•

