



## SPECIFICATION

Model	MV-206	MV-306	MV-406	MV-606
<b>Travel</b>				
X axis mm (inch)	2000 (79)	3000 (118)	4000 (157)	6000 (236)
Y axis mm (inch)	600 (24)	600 (24)	600 (24)	600 (24)
Z axis mm (inch)	550 (22)	550 (22)	550 (22)	550 (22)
<b>Spindle</b>				
Spindle range (rpm)	10,000	10,000	10,000	10,000
Spindle drive	Direct-coupled	Direct-coupled	Direct-coupled	Direct-coupled
<b>Table</b>				
Table size mm (inch)	2500x600 (98x24)	3500x600 (138x24)	4500x600 (177x24)	3500x600 (256x24)
Max. table loading kg (lbs)	1000 (2200)	1000 (2200)	1000 (2200)	1000 (2200)
<b>Feed Rate</b>				
X/Y/Z Rapid feed mm(inch)/min	30000/30000/15000 (1181/1181/591)			
X/Y/Z Feedrate mm(inch)/min	1~7500 (395)	1~7500 (395)	1~7500 (395)	1~7500 (395)
<b>ATC</b>				
Magazine type	Cam	Cam	Cam	Cam
Magazine capacity	24	24	24	24
<b>Tool</b>				
Tool shank	BT.40	BT.40	BT.40	BT.40
<b>Machine size</b>				
Machine height (mm)	3100 (122)	3100 (122)	3100 (122)	3420 (135)
Floor space (mm)	6200 x 3400 (244x134)	7200x3400 (283x134)	8200x3400 (323x134)	9600x3140 (378x124)
Machine weight (kgs)	14000 (551)	14000 (551)	21000 (827)	21000 (827)

( ) optional specification

Specifications are subject to change without notice

